

Special Features

- ▲ VANDAL RESISTANT DESIGN
- ▲ HYGIENIC CREVICE FREE
ONE PIECE CONSTRUCTION
- ▲ SUPPORT LEGS FOR EXTRA STRENGTH

Description

The multiple bowl unit is supplied in four standard lengths with wall mounting brackets. Up to four bowls can be incorporated in a single unit. For added installed strength the multiple bowl unit is available with optional front support legs.

Construction

The multiple bowl unit is manufactured in one piece without joints or crevices from grade 304 stainless steel, with all exposed surfaces polished to a satin finish. The top of the bowl unit is formed with a rear upstand and turned down ends and front edge.

Up to four bowls can be incorporated in the unit top. Units with five or more bowls are supplied as separate assemblies for bolting together on-site. Wall mounting brackets are supplied as standard. Optional front support legs for added installed strength are also available. Each bowl is produced with either one or two tap holes and is supplied as standard with an unslotted flush grated waste fitting.

Options

- ▲ Front support legs.
- ▲ Non-standard waste fitting.
- ▲ Non-standard tap hole sizes.
- ▲ Water controllers, taps and valves (see catalogue section 6).



Technical Specification: Multiple Bowl Unit

Waste Outlet

Each bowl is supplied as standard with a 32 mm (1¼ in) BSP unslotted flush grated waste fitting.

As an alternative to the standard waste fitting the following non-standard fitting can be supplied:

32 mm (1¼ in) BSP unslotted waste, plug, chain and stay.

Tap Hole Positions

Each bowl is produced with either one central or two tap holes.

Tap Hole Sizes

The standard sizes are 30 mm diameter for a central tap hole or 22 mm diameter for two tap holes.

Non-standard sizes that can be provided are:

35 mm dia., 38 mm dia. and 23.5 mm square.

Standard Lengths/Number of Bowls/Support Legs

Standard Length	1200 mm	1800 mm	2400 mm
Number of Bowls	2	3	4
Number of Support Legs	3	4	5

Product Code Selection for Order or Quotation

1. Base Product Code

☐ 262-multiple bowl unit

2. Length

☐ 1200-(2 bowls)

☐ 1800-(3 bowls)

☐ 2400-(4 bowls)

5. Tap Hole Size

Standard

☐ 22-22 mm dia. (if code T selected)

☐ 30-30 mm dia. (if code C selected)

Non-Standard

☐ 35-35 mm dia.

☐ 38-38 mm dia.

☐ 23-23.5 mm sq.

3. Waste Outlet

Standard

☐ 3-unslotted flush grated

Non-Standard

☐ 4-unslotted plug chain and stay

6. Option

☐ FL-front support legs

For details of water controllers, taps and valves see catalogue section 6.

4. Tap Hole Position

☐ C-central

☐ T-two

