



Special Features

- ▲ HYGIENIC NO TOUCH OPERATION
- ▲ VANDAL RESISTANT CASING
- ▲ STAINLESS STEEL OR WHITE GLOSS FINISH
- ▲ SPACE SAVING COMPACT DESIGN
- ▲ HIGH OUTPUT HEATER AND FAN FOR FASTER DRYING
- ▲ BRITISH SAFETY COUNCIL AND CE APPROVED

Description

The high output hand drier offers the user exceptionally fast hand drying and hygienic "No Touch" operation. Designed to be compact and space saving the drier is available with either a stainless steel cover or die cast aluminium cover with a white chip proof finish.

Construction

The hand drier cover is manufactured from either stainless steel or pressure die cast aluminium finished in a white chip proof gloss. Mounted onto the galvanised steel chassis is an infra red controlled printed circuit board and a high volume geometrically designed fan. The high output fan and the design of the air outlet provides high velocity warm air for fast hand drying. The heater element is provided with thermal overload protection and the fan motor is fitted with extra long life carbon bushes. An abuse control system is incorporated in the printed circuit board that automatically switches the drier off after 60 seconds if the outlet is obstructed.

Operation

The hand drier is fitted with an infra red sensor that provides hygienic no touch operation. The drier is switched on automatically when the user's hands are placed under the air outlet. Removal of the hands switches the drier off.

Standards

The hand drier has both CE and British Safety Council approval.

Installation

The hand drier should be installed level, at the required height and securely fixed to the wall. Detailed installation instructions are supplied with the product.



Technical Specification: Hand Drier

5 Brearley Court, Baird Road, Waterwells Business Park, Quedgeley, Gloucester GL2 2AF Tel: 01452 721211 Fax: 01452 721231 Web: www.acornpowell.co.uk

Electrical Supply

220-240 VAC 50/60 Hz.

Insulation

Class 1.

Motor Speed

5500 RPM - hand drier with white cover.

2700 RPM - hand drier with stainless steel cover.

Heat Output

2.6 KW - hand drier with white cover.

1.82 KW - hand drier with stainless steel cover.

Drying Time

27 seconds - hand drier with white cover.

30 seconds - hand drier with stainless steel cover.

Operation

Infra red sensor.

Noise Level

74 dB - hand drier with white cover.

65 dB - hand drier with stainless steel cover.

Product Code Selection for Order or Quotation

1. Base Product Code

731-hand drier with white cover

732-hand drier with stainless steel cover

